








marmoleum Commercial Cleaning - General

Mechanical	Minimum Frequency	Equipment	Cleaning Product	Cleaning Method	Comments
Initial clean	After Installation	  3M Red Pad #5100	Neutral Detergent PH 6-8 (Forbo Monel or equivalent)	Remove surface debris by sweeping, vacuuming or dust mopping - Damp mop floor with neutral detergent and pick up dirty water with mop/squeegee or wet vac if not using an autoscrubber. Rinse with damp clean mop, collect water allow to dry.	If Cement dust is present 2% citric or acetic acid may be used. If desired dry/spray buff the floor with red pad 150-300 rpm rotary machine.
Regular Cleaning	Daily	  3M Red Pad #5100	Neutral Detergent PH 6-8 (Forbo Monel or equivalent)	Remove surface debris by sweeping, vacuuming or dust mopping -Damp mop floor with neutral detergent and pick up dirty water with mop/squeegee or wet vac if not using an autoscrubber. Allow to dry.	Daily depends on level of use and application. Remove spills and stains with damp mop/cloth and neutral detergent.
Occasional Cleaning	As needed depending on use	   3M Top line Auto scrubber pad #5000	Neutral Detergent PH 6-8 (Forbo Monel or equivalent)	Remove surface debris by sweeping, vacuuming or dust mopping - Damp mop floor with neutral detergent if not using an autoscrubber. For medium to heavy soiling use a 3M Topline autoscrubber pad #5000 or 3M blue cleaner pad #5300. Rinse with cool water and pick up with autoscrubber/wet vac. Allow to dry. Spray buff with rotary machine and red pad 150-175RPM or dry buff with 3m Eraser pad #3600 followed by a dust mop.	Use of black or brown pads is not recommended. No need to flood the floor.

CAUTION: Marmoleum with Topshield Two can be damaged by traditional aggressive wet stripping methods and high PH chemicals. If the above floor care instructions are followed wet stripping will not be necessary. Topshield Two is occupancy ready and should not be removed by abrasive burnishing. Use of black or brown pads is not recommended. If high gloss or a sealer is requested by the client an acrylic based floor finish can be applied, not urethane based finishes. Barrier entrance systems such as Coral should be used. Consult Forbo Technical services for more information.

www.forbo-flooring.com.au, Email: info.au@forbo.com