

INTER-TAC ADHESIVE

SUMMARY DATA SHEET

Description:

- Inter-Tac is a pressure sensitive compound
- Inter-Tac has been developed by Interface and is the recommended adhesive for ALL Interface branded carpet tile installations, unless Interface tac-tiles are being used.
- Inter-Tac has been specifically formulated in a green colour for easy differentiation
- Inter-Tac should be used as a complete coverage application for all Interface modular carpet tile.

Application:

- short nap paint roller
- V1 notched trowel for installations requiring a stronger bond

Coverage:

- 10 – 14m² per litre for 100% coverage when using short nap paint roller
- 5m² per litre for 100% coverage when using a V1 notched trowel

Above figures will vary depending on the porosity of the sub floor. On nonporous substrates (e.g. access floors) the rate of coverage will increase.

Notes:

- Adhesive application should not commence until moisture and PH readings of the subfloor have been taken and the subfloor deemed within specified requirements. If the subfloor moisture or PH readings are higher than recommended the installation is not to commence until remedial action is taken.
- An approved sealer must be used on all porous substrates
- It is mandatory that Inter-Tac be allowed tack up before floor covering is installed. Colour will change from green to clear.
- For a stronger bond to the subfloor, carpet tile can be installed into semi-tacked up Inter-Tac allowing some adhesive transfer to occur.

Storage:

- Shelf life is 12 months
- Store between 10~35°C. Do not allow the adhesive to freeze

Clean up:

- Equipment and services should be cleaned **before the adhesive dries**. Clean with water preferably containing some neutral detergent.

IMPORTANT: Users assume all risk and liability resulting from the use of Inter-Tac. It is recommended that users carry out project specific trials to confirm the suitability and application of Inter-Tac.