

Product Information Declaration

nora[®]
by **Interface**[®]

norament 825

Document Version	V1 - December 2023
Product Class	Class 1
Category	Flooring
Product Type	Rubber Tile
Manufacturer	Interface, Inc.
Product	norament
Ranges	Various options available, see www.nora.com for options
Identifier	825
Format/s	Thickness: 3.2 mm Pastilles: 501 mm x 501 mm
Materials	Natural and synthetic rubber, minerals from natural sources and colour pigments
Area of use	norament 825 is suitable for use in heavy-traffic areas. Norament 825 is Commercial General use (Class 32) and Industrial use 41.

Conditions of use

norament 825 must be installed by a qualified trades person in accordance with FloorNZ's Best Practice Guidelines to meet NZS/AS 1884:2013 - Floor Coverings: Resilient Sheet and Tiles - Installation practices and must be installed in accordance with nora's recommended procedures and instructions, including and without limitation nora's subfloor moisture and requirements and initial floor preparation procedures, all as set out in the nora Installation Guide and Cleaning and Maintenance Guide. norament 825 must be cleaned and maintained as per the nora Cleaning and maintenance guide.

At the time of installation and of adhesive bonding, the subfloor temperature must be at least 15° C. Ensure that the norament® floorings have the required subfloor temperature. Especially in winter time, norament® floor coverings have to be stored on site for several days.

Stairs must have a stair nosing fitted with appropriate safety strip.

New Zealand Building Code Compliance

Section of Code	Product Compliance															
<p>B2 Durability</p> <p>B2 3.1 Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or: (c) 5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.</p>	<p>norament 825 tiles have a Standard Product Warranty of 15 years.</p> <p>They are produced in accordance with ISO 9001:2015 Quality Management Systems and ISO 14001:2015 Environmental Management Systems, requirements.</p> <p>Refer to: nora 15-year Standard Product Warranty, norament 825 Technical Specification, norament 825 Installation guide, norament Care & Maintenance documentation for further information.</p>															
<p>C3 Surface Linings</p> <p>C3.4 (b) floor surface materials in the following areas of buildings must meet the performance criteria specified below: Area of building minimum critical radiant flux when tested to ISO 9239-1: 2010.</p> <table border="1" data-bbox="81 1050 783 1877"> <thead> <tr> <th data-bbox="81 1050 325 1245">Area</th> <th data-bbox="328 1050 560 1245">Buildings not protected with an automatic fire sprinkler system</th> <th data-bbox="563 1050 783 1245">Buildings protected with an automatic fire sprinkler system</th> </tr> </thead> <tbody> <tr> <td data-bbox="81 1249 325 1435">Sleeping areas and exitways in buildings where care or detention is provided</td> <td data-bbox="328 1249 560 1435">4.5 kW/m²</td> <td data-bbox="563 1249 783 1435">2.2 kW/m²</td> </tr> <tr> <td data-bbox="81 1440 325 1543">Exitways in all other buildings</td> <td data-bbox="328 1440 560 1543">2.2 kW/m²</td> <td data-bbox="563 1440 783 1543">2.2 kW/m²</td> </tr> <tr> <td data-bbox="81 1547 325 1709">Firecells accommodating more than 50 persons</td> <td data-bbox="328 1547 560 1709">2.2 kW/m²</td> <td data-bbox="563 1547 783 1709">1.2 kW/m²</td> </tr> <tr> <td data-bbox="81 1713 325 1877">All other occupied spaces except household units</td> <td data-bbox="328 1713 560 1877">1.2 kW/m²</td> <td data-bbox="563 1713 783 1877">1.2 kW/m²</td> </tr> </tbody> </table>	Area	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m ²	2.2 kW/m ²	Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²	Firecells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²	All other occupied spaces except household units	1.2 kW/m ²	1.2 kW/m ²	<p>norament 825 maintains a valid test report showing Critical Radiant Flux (CRF) value over 4.5kW/m² meeting all levels of C3 requirements.</p>
Area	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system														
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m ²	2.2 kW/m ²														
Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²														
Firecells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²														
All other occupied spaces except household units	1.2 kW/m ²	1.2 kW/m ²														
<p>D1 Access Routes</p> <p>D1.3.3 Access routes shall: (d) have adequate slip-resistant walking surfaces under all conditions of normal use.</p>	<p>norament 825 is an acceptable solution for dry and wet level areas with a slip resistance rating of R9, It is compliant for access routes as per the D1 3.3. Refer to the norament Slip Reports for further information.</p>															

Section of Code	Product Compliance
<p>F2 Hazardous Building Materials</p> <p>F2.3.1 The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.</p>	<p>No components within norament 825 are considered Hazardous. Refer to the Material Safety Data Sheet and VOC Report for norament Rubber documents.</p>
<p>G3 Food preparation and prevention of contamination</p> <p>G3.3.2 Spaces for food preparation and utensil washing shall have: (b) all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents .</p> <p>G6 Airborne and Impact Sound</p> <p>G6.3.1 The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.</p> <p>G6.3.2 The Impact Insulation Class of floors shall be no less than 55.</p>	<p>G3.3.2 norament 825 is easily cleaned as per the nora cleaning and maintenance guide. nora rubber has low VOC'S, inhibits bacterial growth and is Phthalate free.</p> <p>G6.3.1 & 6.3.2 norament 825 has a footfall sound absorption of 9 dB. Test results like this are an indication only, and a field test with the subfloor and ceiling assembly needs to be performed to ensure the IIC value of 55 is reached for each individual project application.</p>
<p>Warnings & Bans</p>	<p>This product is not subject to any warnings or bans under section 26 of the Building Act 2004</p>

Supporting Documentation

For all specification, installation, care & maintenance, warranty, tests reports and other supporting documentation, refer to www.inzide.co.nz

Contact Details

Product Manufacturer

nora Solutions Inc.
www.nora.com

Manufacturing sites:

nora systems GmbH Hühnerweg 2-4 69469 Weinheim

New Zealand Supplier

Inzide Commercial Ltd.
Level 2, 34 Barry's Point Road
Takapuna, 0632
0800 800 656
www.inzide.co.nz
sales@inzide.co.nz

NZBN: 714832

Responsible Person

In accordance with regulation 8, as the responsible person, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.



Signed for and on the behalf of Inzide Commercial Ltd and nora Inc.

Steve Aschebrock
Managing Director,
Inzide Commercial Ltd.

10/12/2023