






Installation Method




Ashlar




Brick



Non Directional



Quarter turn



Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Walk About **Colour** Pumice **Collection** Look Both Ways Collection

Product Specifications

| | |
|---------------------------------|--|
| Product Number | A014 |
| Product Construction | High Performance Luxury Vinyl Tile |
| Wear Layer Thickness | 0.55 |
| Total Thickness (Metric) | 4.5 mm |
| Classification | EN 651 Class 42 (light industrial general) EN 651 Class 33 (heavy contract) |
| Acoustic Impact Noise Reduction | ISO 140.8 ΔLw = 16dB |
| Finish | CERAMOR+™ UV Stabilized Ceramic Bead Coating |
| Nominal Dimensions | 50cm x 50cm |

Performance Specifications

| | |
|-------------------------|-----------------------------------|
| Critical Heat Flux | AS ISO 9239-1 >7kW/m ² |
| Smoke Rate | AS ISO 9239-1 <750%.min |
| Size, Tolerance | ISO 24342 > 400 mm < 0.35 mm |
| Dimensional Stability | ISO 23999 <0.25% |
| Thickness | ISO 24346 Average value + 0.20mm |
| Resistance to Light | ISO 105-B02 ≥6 |
| Resistance to Heat | ASTM F1514 ΔE< 8 avg Max |
| Resistance to Chemicals | EN-ISO 26987 Passes |
| Reaction to Fire | EN ISO 13501-1 Class BFI-S1 |
| VOC Test | ISO 10580 Pass |
| Flexibility | ISO 24344 Method A Pass |
| Static Load | ASTM F970 ≤0.005" with 1500 psi |
| Castor chair | ISO 4918 Pass |
| Thermal Conductivity | EN 12667 0.16 W/mK |
| Static Electrical | EN 1815 <2kV |
| Slip Resistance | AS 4586:2013 R10, P3 |

Environmental Specifications

| | |
|------------------------------------|--|
| Ingredients and Life Cycle Impacts | View our Environmental Product Declarations |
| Sustainability Assessment | NSF/ANSI 332, Meets Certification Guidelines |
| LEED v4 | Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR |
| End of Life | Fully Recyclable LVT to Carpet Tile Backing Recycling |

Technical Information

| | |
|--------------|--|
| Installation | See Interface LVT Installation Guidelines online |
| Maintenance | See Interface LVT Installation Guidelines online |
| Reclamation | View details on our ReEntry™ Program |
| Warranty | 15 Year Standard LVT Product Warranty |