


allura[®] flex

Installation Instructions



Preparing the Sub floor for Flex Design

The quality of the finished installation will depend on the quality of the sub floor.
In principle what is felt by the hand will be seen by the eye.

Irregularities in the subfloor will be apparent in the finished flooring. All subfloors should be smooth, sound clean and dry in accordance with New Zealand Standard NZS 1884-2013 "Floor coverings - Resilient sheet and tiles – Installation practices."

Acclimatisation

Prior to installation, boxes of tiles should be removed from the delivery pallet and stored not more than five boxes high in the laying area. Material must be acclimatised between 18°C to 27°C for at least 24 hours before installation and the temperature maintained during laying.

The conditioning time should be extended to 48 hours if materials have been stored or transported at temperatures less than 10°C immediately prior to delivery.

Installation Planning

Most Allura Flex designs are non-directional; however the following installation recommendations are given:


Traditional wood design planks do not require mixing from carton to carton (shuffling) prior to installation. Dry laying will identify the best use of design and any possible shade variation between the cartons of material.

Design


Flex Wood
Flex Stone
Flex Sand
Flex Colour
Flex Textile

Installation Methods


Broadloom, Brick, Herringbone
Broadloom, Brick
Broadloom, Brick
Broadloom, Brick
Chequerboard only



Broadloom



Brick



Chequerboard

Installation

Allura Flex tile and plank should be installed using a permanent vinyl adhesive. Adhesive must be applied according to manufacturer's instructions.

Ensure that each tile butts up to its neighbour as firmly (net) as possible without causing edge peaks, cut the perimeter tiles firmly against the wall. Roll completed installation with a minimum 34kg, 2 - 3 wheeled roller.

Areas that could be affected by intense heat magnification from direct sunlight passing through window areas – Use a 2 part epoxy adhesive.

Finish

To show a professional end result, the floor can be finished with skirtings, stair nosings or transitional profiles.

For more information please contact your INZIDE representative or call 0800 800 656

Australia

Forbo Flooring Systems
23 Ormsby Place
Wetherill Park
NSW, 2164

T: 1800 224 471
F: 1800 662 566
info.au@forbo.com
www.forbo-flooring.com.au

New Zealand

INZIDE Commercial
T: 0800 800 656
Email: enquiries@inzide.co.nz
www.inzide.co.nz