




**Installation Method**



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Criterion Classic Woodgrains    **Colour** Washed Maple

**Product Specifications**

Product Number	C001
Product Construction	Luxury Vinyl Plank
Wear Layer Thickness	0.55
Total Thickness (Metric)	3.0 mm
Classification	ASTM F1700 / Class III Printed Vinyl Tile
Finish	CERAMOR™ UV Stabilized Ceramic Bead Coating
Nominal Dimensions	12.5cm x 100cm

**Performance Specifications**

Critical Heat Flux	AS ISO 9239-1 >7kW/m2
Size, Tolerance	ASTM F2055 Passes, ± 0.016 in. per linear foot
Thickness	ASTM F386 Passes
Resistance to Light	ASTM F1515 Passes
Resistance to Heat	(ASTM F1514) Passes
Resistance to Chemicals	ASTM F925 Passes
Flexibility	ASTM F137 Passes
Static Load	ASTM F970 ≤0.005" with 1500 psi
Static Electrical	EN 1815 <2kV
Slip Resistance	AS 4586:2013 R10, P2

**Environmental Specifications**

Ingredients and Life Cycle Impacts	3.0 mm
Sustainability Assessment	Greentag GreenRate Level A GREENGUARD Gold NSF/ANSI 332 Silver
LEED v4	Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR

**Technical Information**

Installation	<a href="#">See Interface LVT Installation Guidelines online</a>
Maintenance	<a href="#">See Interface LVT Installation Guidelines online</a>
Reclamation	<a href="#">View details on our ReEntry™ Program</a>
Warranty	10 Year Standard LVT Product Warranty