

Product Information Declaration

nora[®]
by **Interface**[®]

nora stepfix 240

Document Version	V1 - December 2023
Product Class	Class 1
Category	Flooring
Product Type	Adhesive
Manufacturer	Interface, Inc.
Product	nora stepfix 240
Ranges	Various options available, see www.nora.com for options
Identifier	stepfix 240
Format/s	Dimension of rolls: 240 mm x 50 m = (12 m ²)
Materials	Double-sided adhesive tape with a filament carrier, coated with polyacrylate adhesives of different strengths, and covered with silicone paper.
Area of use	nora stepfix 240 is an adhesive tape solution intended to exclusively be used with norament Rubber stairtreds. These are suitable for heavy commercial use in internal, dry areas.

Conditions of use

Stepfix 240 must be installed by a qualified trades person and in accordance with FloorNZ's Best Practice Guidelines and must be handled, installed, and maintained in strict compliance with nora's recommended procedures and instructions, including and without limitation nora's subfloor moisture and requirements and initial floor preparation procedures, all as set out in the nora Installation Guide and Cleaning and Maintenance Guide.

The installation area must be fully enclosed, weather tight, and climate controlled between 17°C and 24°C and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation. Substrate Requirements: Concrete, wood, metal, and existing floors (existing floors must be only one layer and non-cushioned back).

New Zealand Building Code Compliance

Section of Code			Product Compliance															
<p>B2 Durability</p> <p>B2 3.1 Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or: (c) 5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.</p>			<p>Stepfix 240 has a standard product warranty of 15 years and is produced in accordance with ISO9001:2015 Quality Management Systems and ISO14001:2015 Environmental Management Systems, requirements. Refer to the nora 15-year Standard Product Warranty, Installation, and Care & Maintenance documentation for further information.</p>															
<p>C3 Surface Linings</p> <p>C3.4 (b) floor surface materials in the following areas of buildings must meet the performance criteria specified below: Area of building minimum critical radiant flux when tested to ISO 9239-1: 2010.</p> <table border="1"> <thead> <tr> <th>Area</th> <th>Buildings not protected with an automatic fire sprinkler system</th> <th>Buildings protected with an automatic fire sprinkler system</th> </tr> </thead> <tbody> <tr> <td>Sleeping areas and exitways in buildings where care or detention is provided</td> <td>4.5 kW/m²</td> <td>2.2 kW/m²</td> </tr> <tr> <td>Exitways in all other buildings</td> <td>2.2 kW/m²</td> <td>2.2 kW/m²</td> </tr> <tr> <td>Firecells accommodating more than 50 persons</td> <td>2.2 kW/m²</td> <td>1.2 kW/m²</td> </tr> <tr> <td>All other occupied spaces except household units</td> <td>1.2 kW/m²</td> <td>1.2 kW/m²</td> </tr> </tbody> </table>			Area	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m ²	2.2 kW/m ²	Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²	Firecells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²	All other occupied spaces except household units	1.2 kW/m ²	1.2 kW/m ²	<p>Nora norament rubber is tested as a system with its recommended adhesive options. Refer to the individual CRF Fire test results for the nora norament flooring solution which stepfix 240 is to be used with.</p> <p>Nora, norament Rubbers maintain valid test reports showing Critical Radiant Flux (CRF) value over 4.5kW/m² meeting all levels of C3 requirements.</p>
Area	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system																
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m ²	2.2 kW/m ²																
Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²																
Firecells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²																
All other occupied spaces except household units	1.2 kW/m ²	1.2 kW/m ²																

Section of Code	Product Compliance
<p>F2 Hazardous Building Materials</p> <p>F2.3.1 The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.</p>	<p>No components within stepfix 240 are considered Hazardous.</p> <p>Refer to the Material Safety Data Sheet and VOC Report for stepfix 240 documents.</p>
<p>Warnings & Bans</p>	<p>This product is not subject to any warnings or bans under section 26 of the Building Act 2004</p>

Supporting Documentation

For all specification, installation, care & maintenance, warranty, tests reports and other supporting documentation, refer to www.inzide.co.nz

Contact Details

Product Manufacturer

nora Solutions Inc.
www.nora.com
Manufacturing sites:

nora systems GmbH Höhnerweg 2-4 69469 Weinheim

New Zealand Supplier

Inzide Commercial Ltd.
Level 2, 34 Barry's Point Road
Takapuna, 0632
0800 800 656
www.inzide.co.nz
sales@inzide.co.nz

NZBN: 714832

Responsible Person

In accordance with regulation 8, as the responsible person, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.



on the behalf of Inzide Commercial Ltd and nora Inc.

Steve Aschebrock
Managing Director,
Inzide Commercial Ltd.

10/12/2023