


















Technical specifications

Desktop meets the requirements of EN 688

desktop

	Total Thickness	EN-ISO 24346	2.0 mm
	Roll Width	EN-ISO 24341	1.83 m / 2.0 - Nero only
	Roll Length	EN-ISO 24341	≤ 30 m
	Collection size		21 colourways
	Total Weight	EN-ISO 23997	< 2.1 kg/m ²
	Indentation-residual	EN-ISO 24341-1	< 0.20 mm
	Light fastness	EN-ISO 105B02	Method 3: blue scale minimum 6
	Gloss level	ISO 2813	<5
	Fire Behaviour	AS 3837	Group 3
	Flexibility	EN - ISO 24344	ø 50 mm
	Resistance to chemicals	EN - ISO 26987	Resistant to diluted acids, oils, fats and to conventional solvents. Not resistant to prolonged exposure to alkalis.
	Heat resistance		70 °C
	Body voltage	EN 1815	< 2kV
	Creating better environments		
	renewable electricity	Furniture linoleum is manufactured using 100% electricity from renewable sources.	
	recycled content	Furniture linoleum contains 28% recycled content by weight	
	Life cycle Assessment	LCA is the foundation for securing the lowest environment impact.	

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
 All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
 The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.



DOWNLOADS:

- Furniture linoleum brochure
- Furniture linoleum cleaning & maintenance
- Furniture linoleum | fire report (walls) AS 3837
- Furniture linoleum GECA certificate
- 5 Year Commercial Warranty Form