

























TECHNICAL SPECIFICATIONS

Marmoleum modular meets the requirements of EN-ISO 24011

	Total thickness	EN-ISO 24346	2.50 mm					
	Domestic: heavy	EN-ISO 10874	Class 23					
	Commercial: very heavy	EN-ISO 10874	Class 34					
	Light Industrial: heavy	EN-ISO 10874	Class 43					
	Dimensions (length x width)	EN-ISO 24342	25 x 25 cm	50 x 25 cm	50 x 50 cm	75 x 50 cm	100 x 15 cm	100 x 25 cm
	Number of m ² per box		2.5m ² (40 pcs)	5m ² (40 pcs)	5m ² (20 pcs)	3m ² (8 pcs)	3m ² (20 pcs)	3m ² (12 pcs)
	Squareness and straightness	EN-ISO 24342	≤ 0.25 mm	≤ 0.35 mm	≤ 0.35 mm	≤ 0.35 mm	≤ 0.35 mm	≤ 0.35 mm
	Indentation residual	EN-ISO 24343-1	≤ 0.15 mm					
	Castor chair continuous use	EN 425	Suitable for office chairs with castors					
	Light fastness	EN-ISO 105-B02	Method 3: blue scale minimum 6					
	Resistance to chemicals	EN-ISO 26987	Resistant to diluted acids, oils, fats and to conventional solvents. Not resistant to prolonged exposure to alkalis					
	Bacteriostatic properties		Marmoleum has natural bacteriostatic properties, which are confirmed by independent laboratories, even against the bacteria MRSA					
	Cigarette resistance	EN 1399	Marks left on linoleum as a result of stubbed-out cigarettes can be removed					
	Slip resistance	DIN 51130	R9					
	Acoustical impact sound reduction	EN ISO 717-2	≤ 5 dB					
	Creating better environments							
	Renewable Electricity	Marmoleum Modular is manufactured using 100% electricity made from renewable sources						
	Natural	Marmoleum Modular is produced using 88% natural raw materials, 76% of which are rapidly renewable.						
	Recycled content	Marmoleum Modular contains 58% recycled content by weight						
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor						
	Ska	Marmoleum Modular meets the Ska Rating criteria for M12 soft floor coverings in both office and retail schemes						
	Life Cycle Assessment	LCA is the foundation for securing the lowest environmental impact						
	Installation method	For an optimal result it is advised to install squares tessellated (quarter turned). Rectangles can be laid tessellated and broadloom.						
Marmoleum meets the requirements of EN 14041		EN 14041  0200203-DoP-306						
	Reaction to fire	EN 13501-1	Cfl-s1					
	Slip resistance	EN 13893	DS: ≥ 0.30					
	Body voltage	EN 1815	< 2 kV					
	Thermal conductivity	EN 12524	0.17 W/m-K					

Our recommended adhesive for Marmoleum modular is 646 Eurostar Premium or 414 Euroflex Lino Plus. Marmoleum modular does not require welding. Please contact customer service for more information.