

Product Information Declaration

nora[®]
by **Interface**[®]

nora stairwell solutions

Document Version	V1 - December 2023
Product Class	Class 1
Category	Flooring
Product Type	Rubber
Manufacturer	Interface, Inc.
Product	nora stairwell solutions
Ranges	Various options available, see www.nora.com for options
Identifier	Arago stairtreads, grano stairtreads, hammered stairtreads, pastilles stairtreads, satura stairtreads, 920 stairtreads
Format/s	Various. Refer to the nora stairtread brochure for format options and accessories options such as stair nosing's.
Materials	natural and synthetic rubber, mineral fillers and colour pigments
Area of use	Nora stairwell solutions are suitable for interior use only, in normally dry areas. They are rated for commercial general purpose through to Heavy Duty use.

Conditions of use

Nora Stairwell Solutions must be installed by a qualified trades person in accordance with FloorNZ's Best Practice Guidelines to meet NZS/AS 1884:2013 – Floor Coverings: Resilient Sheet and Tiles – Installation practices and must be installed in accordance with nora's recommended procedures and instructions, including and without limitation nora's subfloor moisture and requirements and initial floor preparation procedures, all as set out in the nora Installation Guide and Cleaning and Maintenance Guide. nora Stairwell Solutions must be cleaned and maintained as per the nora Cleaning and maintenance guide.

nora Stairwell Solutions are intended for use on internal angled or straight stairs. This all-in-one nosing, tread and riser makes installation simple and efficient and is to be installed with nora[®] stepfix™ 240 doublesided tape to provide an immediate trafficking solution. These are designed for multiple flooring thicknesses; they can be used on noraplan or norament floor coverings. Once the flooring is pre-cut to the dimension of an individual stair tread, the nora stair nosing insertion lip locks the flooring into place and protects the cut edge. nora stair nosing are both impact and shock resistant and available in different formats, colours, or textures.

New Zealand Building Code Compliance

Section of Code	Product Compliance															
<p>B2 Durability</p> <p>B2 3.1 Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or: (c) 5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.</p>	<p>nora stair tread solutions have a standard product warranty of 15 years. They are produced in accordance with ISO9001:2015 Quality Management Systems and ISO14001:2015 Environmental Management Systems, requirements.</p> <p>Refer to the nora 15-year Standard Product Warranty, Installation, and Care & Maintenance documentation for further information.</p>															
<p>C3 Surface Linings</p> <p>C3.4 (b) floor surface materials in the following areas of buildings must meet the performance criteria specified below: Area of building minimum critical radiant flux when tested to ISO 9239-1: 2010.</p> <table border="1" data-bbox="81 1048 780 1877"> <thead> <tr> <th data-bbox="81 1048 325 1240">Area</th> <th data-bbox="325 1048 560 1240">Buildings not protected with an automatic fire sprinkler system</th> <th data-bbox="560 1048 780 1240">Buildings protected with an automatic fire sprinkler system</th> </tr> </thead> <tbody> <tr> <td data-bbox="81 1240 325 1435">Sleeping areas and exitways in buildings where care or detention is provided</td> <td data-bbox="325 1240 560 1435">4.5 kW/m²</td> <td data-bbox="560 1240 780 1435">2.2 kW/m²</td> </tr> <tr> <td data-bbox="81 1435 325 1543">Exitways in all other buildings</td> <td data-bbox="325 1435 560 1543">2.2 kW/m²</td> <td data-bbox="560 1435 780 1543">2.2 kW/m²</td> </tr> <tr> <td data-bbox="81 1543 325 1709">Firecells accommodating more than 50 persons</td> <td data-bbox="325 1543 560 1709">2.2 kW/m²</td> <td data-bbox="560 1543 780 1709">1.2 kW/m²</td> </tr> <tr> <td data-bbox="81 1709 325 1877">All other occupied spaces except household units</td> <td data-bbox="325 1709 560 1877">1.2 kW/m²</td> <td data-bbox="560 1709 780 1877">1.2 kW/m²</td> </tr> </tbody> </table>	Area	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m ²	2.2 kW/m ²	Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²	Firecells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²	All other occupied spaces except household units	1.2 kW/m ²	1.2 kW/m ²	<p>nora stair tread solutions are tested as a system with its recommended stairwell solution. Refer to the individual CRF Fire test results for the nora norament flooring solution which stairwell solution is to be used with.</p> <p>All nora, norament rubbers maintain valid test reports showing a Critical Radiant Flux (CRF) value over 4.5kW/m² meeting all levels of C3 requirements.</p>
Area	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system														
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m ²	2.2 kW/m ²														
Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²														
Firecells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²														
All other occupied spaces except household units	1.2 kW/m ²	1.2 kW/m ²														
<p>D1 Access Routes</p> <p>D1.3.3 Access routes shall: (d) have adequate slip-resistant walking surfaces under all conditions of normal use.</p>	<p>Nora stairwell solutions are an acceptable solution for dry and wet level areas. It compliant for access routes as per the D1 3.3. Refer to the norament Slip Reports for further information.</p>															

Section of Code	Product Compliance
<p>F2 Hazardous Building Materials</p> <p>F2.3.1 The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.</p>	<p>No components within nora stairwell solutions are considered Hazardous.</p> <p>Refer to the Material Safety Data Sheet and VOC Report for nora stairwell solution ranges, documents.</p>
<p>G3 Food preparation and prevention of contamination</p> <p>G3.3.2 Spaces for food preparation and utensil washing shall have: (b) all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents.</p> <p>G6 Airborne and Impact Sound</p> <p>G6.3.1 The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.</p> <p>G6.3.2 The Impact Insulation Class of floors shall be no less than 55.</p>	<p>G3.3.2 nora stairwell solutions are easily cleaned as per the nora cleaning and maintenance guide. They are low VOC's and inhibit bacterial growth and are Phthalate free.</p> <p>G6.3.1 & 6.3.2 A field test with the subfloor and ceiling assembly must be performed to ensure the IIC value of 55 is reached for each project application.</p>
<p>Warnings & Bans</p>	<p>This product is not subject to any warnings or bans under section 26 of the Building Act 2004</p>

Supporting Documentation

For all specification, installation, care & maintenance, warranty, tests reports and other supporting documentation, refer to www.inzide.co.nz

Contact Details

Product Manufacturer

nora Solutions Inc.

www.nora.com

Manufacturing sites:

nora systems GmbH Hühnerweg 2-4 69469 Weinheim

New Zealand Supplier

Inzide Commercial Ltd.

Level 2, 34 Barry's Point Road

Takapuna, 0632

0800 800 656

www.inzide.co.nz

sales@inzide.co.nz

NZBN: 714832

Responsible Person

In accordance with regulation 8, as the responsible person, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.



Signed for and on the behalf of Inzide Commercial Ltd and nora Inc.

Steve Aschebrock

Managing Director,

Inzide Commercial Ltd.

10/12/2023