

# **Product Information Declaration**



| Document Version | V1 - December 2023                                                                                                                                                                                                                 |  |  |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| Product Class    | Class 1                                                                                                                                                                                                                            |  |  |
| Category         | Flooring                                                                                                                                                                                                                           |  |  |
| Product Type     | Static Dissipative Vinyl Tiles                                                                                                                                                                                                     |  |  |
| Manufacturer     | Forbo Holdings Ltd.                                                                                                                                                                                                                |  |  |
| Product          | Colorex SD Static Dissipative Vinyl Tiles                                                                                                                                                                                          |  |  |
| Ranges           | Various options available, see ww.forbo.com for options                                                                                                                                                                            |  |  |
| Identifier       | Colorex SD                                                                                                                                                                                                                         |  |  |
| Format/s         | Thickness: 2.00 mm   3.00 mm<br>Tile: 61.5cmx61.5cm                                                                                                                                                                                |  |  |
| Materials        | Comprised of PVC, carbon black and calcium carbonate                                                                                                                                                                               |  |  |
| Area of use      | Forbo Colorex SD is suitable for interior use only, in dry level areas. Commercial Very Heavy Duty Rated use class 34 and Light Industrial Use class 43. Colorex SD Tiles are static dissipative 1x10^6 $\Omega$ - 1x10^8 $\Omega$ |  |  |

#### Conditions of use

Please note that not only do dissipative floors need grounding, but also personnel should wear groundable footwear, e.g. ESD footwear. It is best to consult your ESD Co-Ordinator or a Static Control Specialist to discuss the level of control best suited for your requirements.

The installation of Colorex SD should be carried out in accordance with NZS 1884-2013 "Resilient sheet and tiles laying and maintenance practices." And must be installed by a qualified trades person in accordance with FloorNZ's Best Practice Guidelines and installed in accordance with the Forbo Installation Guide. Forbo Colorex SD is to be installed using a low emission EC1 adhesive is recommended, and always in combination with 801 Eurostrip Copper Tape. Colorex SD must be cleaned and maintained in accordance with the Forbo Colorex Cleaning Guide. Underlays are not suitable for use under Colorex SD.

Forbo Coral Entrance Matting is intended to be used at every entrance and exit point of a building, a distance of 3 meters is recommended. This protects Forbo Colorex SD against excessive soiling from outside contaminants.

www.inzide.co.nz Page 1 of 4

## New Zealand Building Code Compliance

| Section of Code                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                             |                                                                         | Product Compliance                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| B2 Durability B2 3.1 Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or: (c) 5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building. |                                                                             |                                                                         | Forbo Colorex SD Tiles have a Standard Product Warranty of 15 years.  They are produced in accordance with ISO 9001:2015 Quality Management Systems and ISO 14001:2015 Environmental Management Systems, requirements. Refer to: Forbo 15-year Standard Product Warranty, Colorex SD Technical Specification, Forbo Colorex SD/EC Installation guide, Forbo Colorex Care & Maintenance documentation for further information. |
| C3 Surface Linings C3.4 (b) floor surface materials in the following areas of buildings must meet the performance criteria specified below: Area of building minimum critical radiant flux when tested to ISO 9239-1: 2010.                                                                                                                                                                                                                                                                                       |                                                                             |                                                                         | Forbo Colorex SD maintains a valid test report showing a Critical Radiant Flux (CRF) value over 4.5kW/m2 meeting all levels of C3 requirements.                                                                                                                                                                                                                                                                               |
| Area                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Buildings not<br>protected with<br>an automatic<br>fire sprinkler<br>system | Buildings<br>protected with<br>an automatic<br>fire sprinkler<br>system |                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Sleeping areas<br>and exitways in<br>buildings where<br>care or detention<br>is provided                                                                                                                                                                                                                                                                                                                                                                                                                          | 4.5 kW/m²                                                                   | 2.2 kW/m²                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Exitways in all other buildings                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 2.2 kW/m²                                                                   | 2.2 kW/m²                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Firecells<br>accommodating<br>more than 50<br>persons                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 2.2 kW/m²                                                                   | 1.2 kW/m²                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                               |
| All other occupied spaces except household units                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1.2 kW/m²                                                                   | 1.2 kW/m²                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                               |
| D1 Access Routes D1.3.3 Access routes shall: (d) have adequate slip- resistant walking surfaces under all conditions of normal use.                                                                                                                                                                                                                                                                                                                                                                               |                                                                             |                                                                         | Colorex SD is an acceptable solution for Internal, dry areas. It is compliant for access routes as per the D1 3.3. Refer to the Colorex SD Slip Report for further information.                                                                                                                                                                                                                                               |

www.inzide.co.nz Page 2 of 4

| Section of Code                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Product Compliance                                                                                                                                                                      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| E3 Internal Moisture  E3.3.3 Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned. E3.3.5 Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned. E3.3.6 Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces. | Colorex SD is easy to clean. It is impervious and water resistant. Refer to the Colorex Vinyl Cleaning and Maintenance Guide and Colorex Vinyl Installation Guide for more information. |
| F2 Hazardous Building Materials F2.3.1 The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.                                                                                                                                                                                                | No components within Forbo Colorex SD are considered Hazardous. Refer to the Colorex SD Material Safety Data Sheet and VOC Report documents for further information.                    |
| Warnings & Bans                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | This product is not subject to any warnings or bans under section 26 of the Building Act 2004                                                                                           |

### **Supporting Documentation**

For all specification, installation, care & maintenance, warranty, tests reports and other supporting documentation, refer to www.inzide.co.nz

www.inzide.co.nz Page 3 of 4

#### **Contact Details**

#### **Product Manufacturer**

Forbo Flooring Systems www.forbo.com

Manufacturing sites:
Assendelft, The Netherlands
Coevorden, The Netherlands
Giubiasco, Switzerland
Kirkcaldy, Scotland
Reims, France
Krommenie, The Netherlands
Bamber Bridge, United Kingdom
Ripley, United Kingdom
Telford, United Kingdom

#### **New Zealand Supplier**

Inzide Commercial Ltd. Level 2, 34 Barry's Point Road Takapuna, 0632 0800 800 656 www.inzide.co.nz sales@inzide.co.nz

NZBN: 714832

### Responsible Person

In accordance with regulation 8, as the responsible person, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

Signed for and on the behalf of Inzide Commercial Ltd and Forbo Inc.

Steve Aschebrock Managing Director, Inzide Commercial Ltd.

8/12/2023

www.inzide.co.nz Page 4 of 4