

Product Information Declaration

nora[®]
by **Interface**[®]**norament 992**

Document Version	V1 - December 2023
Product Class	Class 1
Category	Floor Coverings
Product Type	Rubber Tiles
Manufacturer	Interface, Inc.
Product	norament
Ranges	Various options available, see www.nora.com for options
Identifier	992 / 992 grano
Format/s	Thickness: 9.0 mm Tiles: 1002 x 1002 mm
Materials	Natural & synthetic rubber, mineral filler and colour pigments
Area of use	norament 992/992 Grano is suitable for dry level areas and is Commercial Very Heavy Duty Rated use class 34 and Industrial Use class 43.

Conditions of use

norament 992 must be installed by a qualified trades person in accordance with FloorNZ's Best Practice Guidelines to meet NZS/AS 1884:2013 - Floor Coverings: Resilient Sheet and Tiles - Installation practices and must be installed in accordance with nora's recommended procedures and instructions, including and without limitation nora's subfloor moisture and requirements and initial floor preparation procedures, all as set out in the nora Installation Guide and Cleaning and Maintenance Guide. norament 992 must be cleaned and maintained as per the nora Cleaning and Maintenance guide.

If using norament on stairs, stairs must have the appropriate stair nosing applied with safety strip. An alternative solution is available from nora specifically for use on stairs called nora staitread.

New Zealand Building Code Compliance

Section of Code	Product Compliance															
<p>B2 Durability</p> <p>B2 3.1 Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or: (c) 5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.</p>	<p>norament 992 has a standard product warranty of 15 years and is produced in accordance with ISO9001:2015 Quality Management Systems and ISO14001:2015 Environmental Management Systems, requirements. Refer to the nora 15-year Standard Product Warranty, Installation, and Care & Maintenance documentation for further information.</p>															
<p>C3 Surface Linings</p> <p>C3.4 (b) floor surface materials in the following areas of buildings must meet the performance criteria specified below: Area of building minimum critical radiant flux when tested to ISO 9239-1: 2010.</p> <table border="1" data-bbox="81 1048 780 1872"> <thead> <tr> <th data-bbox="81 1048 325 1240">Area</th> <th data-bbox="330 1048 558 1240">Buildings not protected with an automatic fire sprinkler system</th> <th data-bbox="563 1048 780 1240">Buildings protected with an automatic fire sprinkler system</th> </tr> </thead> <tbody> <tr> <td data-bbox="81 1247 325 1435">Sleeping areas and exitways in buildings where care or detention is provided</td> <td data-bbox="330 1247 558 1435">4.5 kW/m²</td> <td data-bbox="563 1247 780 1435">2.2 kW/m²</td> </tr> <tr> <td data-bbox="81 1442 325 1541">Exitways in all other buildings</td> <td data-bbox="330 1442 558 1541">2.2 kW/m²</td> <td data-bbox="563 1442 780 1541">2.2 kW/m²</td> </tr> <tr> <td data-bbox="81 1547 325 1704">Firecells accommodating more than 50 persons</td> <td data-bbox="330 1547 558 1704">2.2 kW/m²</td> <td data-bbox="563 1547 780 1704">1.2 kW/m²</td> </tr> <tr> <td data-bbox="81 1711 325 1872">All other occupied spaces except household units</td> <td data-bbox="330 1711 558 1872">1.2 kW/m²</td> <td data-bbox="563 1711 780 1872">1.2 kW/m²</td> </tr> </tbody> </table>	Area	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system	Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m ²	2.2 kW/m ²	Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²	Firecells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²	All other occupied spaces except household units	1.2 kW/m ²	1.2 kW/m ²	<p>norament 992 maintains valid test reports showing Critical Radiant Flux (CRF) value over 4.5kW/m² meeting all levels of C3 requirements.</p>
Area	Buildings not protected with an automatic fire sprinkler system	Buildings protected with an automatic fire sprinkler system														
Sleeping areas and exitways in buildings where care or detention is provided	4.5 kW/m ²	2.2 kW/m ²														
Exitways in all other buildings	2.2 kW/m ²	2.2 kW/m ²														
Firecells accommodating more than 50 persons	2.2 kW/m ²	1.2 kW/m ²														
All other occupied spaces except household units	1.2 kW/m ²	1.2 kW/m ²														
<p>D1 Access Routes</p> <p>D1.3.3 Access routes shall: (d) have adequate slip-resistant walking surfaces under all conditions of normal use.</p>	<p>norament 926 is an acceptable solution for dry level areas. It is compliant for access routes as per the D1 3.3. Refer to the norament Slip Reports for further information.</p>															

Section of Code	Product Compliance
<p>F2 Hazardous Building Materials</p> <p>F2.3.1 The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.</p>	<p>No components within norament Rubber are considered Hazardous. Refer to the Material Safety Data Sheet and VOC Report for norament Rubber documents.</p>
<p>G3 Food preparation and prevention of contamination</p> <p>G3.3.2 Spaces for food preparation and utensil washing shall have: (b) all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents .</p> <p>G6 Airborne and Impact Sound</p> <p>G6.3.1 The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.</p> <p>G6.3.2 The Impact Insulation Class of floors shall be no less than 55.</p>	<p>G3.3.2 norament 992 is easily cleaned and maintained as per the nora cleaning and maintenance guide. It inhibits the growth of bacteria is tested to show low VOC's and is Phthalate free.</p> <p>G6.3.1 & 6.3.2 norament 926 has a high footfall sound absorption of 15dB. However, test results like this are an indication only, and a field test with the subfloor and ceiling assembly needs to be performed to ensure the IIC value of 55 is reached for each individual project application.</p>
<p>Warnings & Bans</p>	<p>This product is not subject to any warnings or bans under section 26 of the Building Act 2004</p>

Supporting Documentation

For all specification, installation, care & maintenance, warranty, tests reports and other supporting documentation, refer to www.inzide.co.nz

Contact Details

Product Manufacturer

nora Solutions Inc.
www.nora.com
Manufacturing sites:

nora systems GmbH Hühnerweg 2-4 69469 Weinheim

New Zealand Supplier

Inzide Commercial Ltd.
Level 2, 34 Barry's Point Road
Takapuna, 0632
0800 800 656
www.inzide.co.nz
sales@inzide.co.nz

NZBN: 714832

Responsible Person

In accordance with regulation 8, as the responsible person, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.



Signed for and on the behalf of Inzide Commercial Ltd and nora Inc.

Steve Aschebrock
Managing Director,
Inzide Commercial Ltd.

10/12/2023